

**CAMARILLO SANITARY DISTRICT PERMIT**

SERVICE DATA		SEWER DATA	Acct.#	FEE
Service Address		<b>Street Lateral</b>		
Name of Owner		*Residential	S1	
Billing Address		*Comm./ Indust.	S3	
Telephone #		<b>Building Lateral</b>		
Contractor		*Commercial	S3	
Address		*Industrial	S3	
Telephone #		*Residential	S1	
<input type="checkbox"/> New Connection <input type="checkbox"/> Existing Connection		<b>Other</b>		
Connecting to: <input type="checkbox"/> Gravity <input type="checkbox"/> Pressure*		Septic Aband.	S6	
<input type="checkbox"/> SDR 26 <input type="checkbox"/> SDR 17 (Trenchless only)		*Sand/Grease Trap		
<input type="checkbox"/> Ductile Iron <input type="checkbox"/> VCP <input type="checkbox"/> Other		*Sample Well		
Size: <input type="checkbox"/> 4" <input type="checkbox"/> 6"		<b>Total Fee</b>		
Comments:		*Must be Approved by CAMSAN		
Contractor/Owner Signature		Fee Received By	Date:	
PW Inspector	Date:	Issued By	Date:	
		CAMSAN Inspector	Date:	

**SKETCH DETAILS OF PROPOSED WORK**



Call (805) -

**48 hours in advance of any work**

**City of Camarillo  
Public Works  
Camarillo Sanitary District**

**Standard Conditions**

Sewer/FOG Permit # \_\_\_\_\_  
Encroachment Permit # \_\_\_\_\_

- All work being performed must comply with the most current (March 2015) Camarillo Sanitary District (CSD) Standard Specifications.
- The assigned Public Works inspector must be notified prior to the start of **any** work.
- **Any** work in the City of Camarillo Right of Way requires an approved Encroachment Permit. This applies to non-excavation work.
- NO ABS Pipe or Fittings will be permitted!
- Commercial Laterals and Connections must be Vitrified Clay Pipe (VCP).
- Cured in Place Pipeline (CIPP) rehabilitation Materials, Specifications, and Certification for Installation must be submitted for review and approval by the CSD.
- Before a Sewer Permit for a CIPP/Liner/Pipe Burst can be issued a high quality video must be submitted to Public Works showing the condition of the existing pipe prior to installation. A high quality video once the CIPP/Liner/Pipe Burst is installed will also be required to close out a permit.
- Installed CIPP/Liners within the City Right of Way must run the length of the lateral to the mainline connection and must not protrude into the CSD sewer main.
- Install any new lines with pipe bedding per standard plate # 12
- Cleanouts are required 2' feet away from the structure and at any change in direction greater than 22.5 degrees, installation per standard plate # 16
- Gravity Pipe Field Closures per standard plate # 20 (Use Strong Back pipe couplings)
- Applicants must inform all persons performing work under this permit of all conditions.

**Applicant's Initials** \_\_\_\_\_